

## Masons Poly Dry-Fix

DPC150  
DPC200  
DPC250  
DPC300  
DPC400



\*DRY-FIX\* is a Polyethylene Dampcourse and Concealed Flashing barrier of impervious material, built in to prevent moisture movement to any part of a building requiring protection. It includes a waterproof strip barrier around an opening in a wall or door or at a roof junction.

\*DRY-FIX\* Rolls are available in Boxes, Pallets or singular rolls.

Product is available labelled to your specification.

Product will be labelled with a Compliance Statement with batch No. length and width of rolls.

Store undercover and enclosed to avoid dust.

### FEATURES

- Unique construction of \*DRY-FIX\* gives instant shape forming
- A replacement for Bitumen Paper
- Does not react with solvent treated timber
- Inert to most solvents
- Permanent life span non-degradable
- Easy to use
- Cost effective

### APPLICATIONS

Used in the building industry to avoid moisture. It provides a complete and permanent moisture barrier in the protection against water damage to buildings through the walls and brickwork. Used around brick vents, timber framing, windows and door flashings.

### TECHNICAL DETAILS

- Manufactured to AS/NZS2904 – 1995
- Type tested – Beal
- Extruded Sheet – Polyethylene material smooth to 500 µm thickness (0.5mm thick)
- Embossed both sides – effective thickness 750 µm (0.75mm thick)
- Impact resistant
- Black Flexible polyethylene Film
- Low Slip with a kinetic coefficient of friction
- Non-Slip as product is double embossed
- Roll core made from recycled plastic materials

Sizes available:

50mm x 30m	75mm x 30m
90mm x 30m	90mm x 50m
100mm x 30m	150mm x 30m
200mm x 30m	250mm x 30m
300mm x 30m	400mm x 30m



MASONS PLASTABRICK

MASONS PLASTABRICK

0800 522 533 [WWW.MASONSPLASTABRICK.CO.NZ](http://WWW.MASONSPLASTABRICK.CO.NZ)

(09) 414 7551 FAX (09) 414 7553 9B PARKHEAD PLACE, ALBANY 0752, AUCKLAND