



MASONS

Waterproofing Agent

MASONS Waterproofing Agent is used to improve the waterproofing properties of cement mortars, plaster/render and concrete.

USES:

MASONS Waterproofing Agent will drastically reduce the transference of moisture through most cement mixes. May be used in any situation where a degree of waterproofing is required in concrete or mortar.

ADVANTAGES:

- Easy to use.
- Durable and long lasting.
- Enhances the waterproofing properties of cement
- Does not affect normal cement properties.

MIXING:

Mix the necessary cement, sand and/or aggregates dry in the usual quantities. Add MASONS Waterproofing Agent to the normal volume of water to be used and stir thoroughly. Add the solution to the dry materials and maintain mixing in the usual manner.

APPLICATION:

Add MASONS Waterproofing Agent to the mixing water for all work.

CONCRETE: Normal concreting practice regarding mixing, placing, bag sizes, curing etc, needs to be followed at all times

PLASTER: It is recommended that all work be done using a two coat method as follows:

1st COAT: A minimum 10mm render of sand and cement with Mason's Waterproofing Agent in the mixing water.

2nd COAT: Build up to the required finished thickness - but not less than 5mm total thickness. The second coat must be applied not later than 24 hours after the first coat.

MIXING WATER



COVERAGE:

Use at the rate of 1 litre per 40 kg bag of cement, for all applications. MASONS Waterproofing Agent is supplied ready for use.

PACKAGING:

MASONS Waterproofing Agent is packed in: 1 litre, 5 litre, 20 litre, and 200 litre drum.

TECHNICAL SERVICE:

For your nearest stockist or additional technical information on MASONS products and our wide range of sealing compounds, concrete admixtures and additives for the construction industry, contact MASONS on 0800 522 533.



MASONS

| 12c Te Kea Place, Albany

| Freephone 0800 522 533