

PLASTABRICK PREMIUM RANGE DECORATIVE TEXTURES

PREMIUM BUILD HIGH BUILD EXTERIOR ACRYLIC PAINT

DESCRIPTION

Premium Build High Build Acrylic Finish is formulated on an adhesion promoted pure acrylic latex that imparts excellent adhesion, water and alkali resistance and exception weather resistance. The low sheen finish will promote good soil resistance and a finish that is easy to clean. The high build properties of this coating enhances application on difficult to apply substrates and produces a very tough finish. A dry film thickness of 80 microns per coat can be achieved.

FEATRUERS AND BENEFITS

- Excellent adhesion and build over Plastabrick Limestop and primed surfaces.
- Quick dry.
- High Water and Alkali resistance
- Excellent weather resistance and low dirt pick up.

LIMITATIONS

- Do not apply when ambient temperature is below 10°C or surface temperature is above 45°C.
- Apply as supplied – do not thin.

TECHNICAL DATA

Resin Type:	Adhesion Promoted Pure Acrylic polymer
Pigmentation:	Titanium dioxide and inert extenders
Solvents:	Water
Colour:	White and pastel tints.
Gloss Level:	Low Sheen.
Density:	1.34 Kgs/ Litre
Dry-Time:	30 mins Touch, 4 hour between overcoat.
Coverage:	4-6 m ² per litre.
No. of coats:	Two
Packaging sizes:	4 & 15 litres
Flash Point:	None
Thinner:	Water

SURFACE PREPARATION

- Remove all unsound paint, surface grease and oil, dirt etc. Treat mould affect areas with Masons Splash and Dash.

APPLICATION

- Apply two coats of PREMIUM BUILD High Build Acrylic Finish to dry film thickness of 80 microns per coat.
- For metal or metal reinforced concrete structures us a specified primer.
- Apply one coat of LIMESTOP Plaster Sealer.

FOR BEST RESULTS

- 1) Ensure correct dry film thickness is achieved.
- 2) Allow at least 4 hours before overcoating.
- 3) Do not apply in direct sunlight.

HEALTH AND SAFETY

- PREMIUM BUILD High Build Acrylic Finish is essentially non-flammable and non-hazardous. (Please refer to Material Safety Data Sheet before using)
- KEEP OUT OF REACH OF CHILDREN

www.plastabrick.org.nz

PLASTABRICK CLADDING SYSTEMS | Freephone 0800 522 533 | PO Box 300 771, Albany, Auckland