

PLASTABRICK PREMIUM RANGE

DECORATIVE TEXTURES

EXTRA COVER ACRYLIC PAINT

DESCRIPTION

- Extra Cover Acrylic is a Premium 100% Acrylic Paint which gives a tough, dirt resistant surface. Excellent gloss retention in early and extended weathering.
- It is ideal for all properly primed and prepared exterior and interior surfaces.
- It is warranted for cracking peeling and flaking for 7 years.

FEATURES AND BENEFITS

- Excellent adhesion to primed and correctly prepared old paintwork.
- Can be used on properly prepared substrate types and may be used for interior and exterior surfaces.
- A durable finish available in gloss, semi-gloss and low sheen.
- Available in a full range of tinted colours.

LIMITATIONS

- Do not apply when ambient temperature is below 10°C or surface temperature is above 40°C.

TECHNICAL DATA

Resin Type:	100% Acrylic Emulsion
Pigmentation:	Oxide pigments and inert extenders
Solvents:	Water
Colour:	White and full range of factory tint bases.
Gloss Level:	Gloss, Semi-gloss and Low sheen.
Density:	1.36 Kgs/ Litre average
Dry-Time:	30 mins Touch, 2 hour overcoat.
Coverage:	12 - 16 m ² per litre.
No. of coats:	Two
Packaging sizes:	4 & 15 litre
Flash Point:	None
Thinner:	Water



SURFACE PREPARATION

- Surface must be thoroughly cleaned to remove all traces of dust, dirt, moss oil and grease, bird droppings etc. All areas of degraded paint and substrate must be sanded smooth and spot primed with All 'n One Primer. Very new galvanised sheet steel must be degreased with Galvoprep – Galvanised iron cleaner, rinsed with clean water, allowed to dry and primed with a Galvanised iron primer. Moss and Mould can be removed with Masons Splash and Dash.

APPLICATION

- Apply two liberal coats at the recommended coverage, allowing at least 2 hours drytime between coats, to the properly prepared surface by Brush or roller or airless spray.
- To keep brushes and rollers working freely rinse occasionally with clean water.
- Apply one coat of LIMESTOP Plaster Sealer.

FOR BEST RESULTS

- 1) Apply the product by Brush to ensure maximum contact with surface.
- 2) With repaints, spot prime with All 'n One Primer, followed by one full coat of the same topcoat.
- 3) On set plaster use Lime Busta
- 4) On porous cement tiles use a Roof sealer.
- 3) Can be overcoated with most acrylic systems.

HEALTH AND SAFETY

- Plastabrick Acrylic Paint is essentially non-flammable and non-hazardous. (Please refer to Material Safety Data Sheet before using)
- KEEP OUT OF REACH OF CHILDREN

www.plastabrick.org.nz

PLASTABRICK CLADDING SYSTEMS | Freephone 0800 522 533 | PO Box 300 771, Albany, Auckland